

SIGNBRIDGE PLUS

40 W LED driver. Model: **BPSP-40-24V.1**



baltled
signage illumination

INPUT

INPUT VOLTAGE RANGE	200 – 240 VAC; 50 – 60 Hz
MAX INPUT AC CURRENT	0.3 A Max
MAX INRUSH CURRENT	≤50 A (100-277 VAC)
POWER FACTOR	≥0.95 (230 VAC)

OUTPUT

OUTPUT CURRENT	1.67 A
OUTPUT VOLTAGE	24 VDC
OUTPUT POWER	40 W

ORDERING INFORMATION

SKU	UNIT NET WEIGHT, G	UNIT DIMENSIONS (LxWxH), MM
BPSP-40-24V.1	450.0	172x44x33


GENERAL SPECIFICATIONS

EFFICIENCY (TYP.)	≥86% (230 VAC)
COLD START	≤3000mS (230 VAC)
TOTAL HARMONIC DISTORTION (THD)	< 20%
OPERATING CONDITIONS	-40 °C ~ +60 °C; 20 ~ 95% humidity
STORAGE CONDITIONS	-40 °C ~ +80 °C; 10 ~ 95% humidity
IP CLASS	IP68
PROTECTIONS INCLUDED	Over voltage Over current Short circuit
WARRANTY	5 years, ≥50 000 h

QUANTITY OF DRIVERS PER CIRCUIT BREAKER

CIRCUIT BREAKER OF TYPE C 16 A
28 units (230 VAC)

DIMENSIONS



* Dimensions are in mm

FEATURES

- Constant voltage mode output
- Metal housing design with functional ground
- Built-in active PFC function
- IP68 rating for indoor or outdoor installations
- Typical lifetime ≥50,000 hours
- 5 years warranty

CONFORMITY & STANDARDS

EMC Emission:

- compliance to EN55015

EMC Immunity:

- EN55015
- EN61547
- EN61000-3-2
- EN61000-3-3
- CB
- CE-LVD:
 - IEC/EN61347-1,
 - IEC/EN61347-2-13,