

EDGELIT SLIM

LED RIGID BAR

5 YEARS WARRANTY

40 - 80

10x30°

6500 K

1500 lm

12.2 W

IP 67

L70 50 000 h



IP67

IP20

ITEM DESCRIPTION

EdgeLit Slim LED rigid bars are specially designed for double-sided lightboxes with depth from 40 to 80 mm and height up to 1500 mm. EdgeLit Slim bar has 6 LEDs coupled with lens and mounted on the aluminum bar. Thanks to that, it takes much less time to install bars than regular LED modules. It is a perfect solution to achieve homogeneous and powerful illuminance of the diffusive surface.

APPLICATION


- Double-sided light boxes
- Recommended depth: 40-80 mm

FEATURES & BENEFITS


- IP67 protection class for outdoor and indoor applications
- IP20 protection class for indoor applications
- 6 mm aluminium base for good heat sinking (for IP67 bar)
- Easy and fast installation
- Long life-span of 50,000 h

GENERAL SPECIFICATIONS

SUPPLY VOLTAGE	24 VDC
POWER, W	12.2W
CRI	70
OPTICS	10x30°
RECCOMENDED DEPTH	40-80 mm
BINNING	3 SDCM
COLOUR / CCT	6500 K
OPERATING TEMPERATURE	-30 °C ~ +50 °C
STORAGE TEMPERATURE	+5 °C ~ +70 °C
CERTIFICATION	CE and RoHS compliant
IP CLASS	IP67 IP20
LIFETIME	L70 50,000 h
WARRANTY	5 years
MOUNTING OPTIONS	IP 67: u shape snap-in clicks IP 20: double-sided tape



LIGHT DISTRIBUTION GRAPH



— CO-180 -- C90-270 10x30°

ORDERING INFORMATION

SKU	IP CLASS	COLOUR	POWER, W	LUMEN OUTPUT, LM	DIMENSIONS, MM	STATUS
BLBP-340A10x3065E12	IP67	6500 K	12.2	1500	345x31x20	PRE-ORDER
BLBP-330A10x3065I12	IP20	6500 K	12.2	1500	330x25x14	IN STOCK
BLBP-CKIT	Additional connector kit					

* Pre-order products will be available only with MOQ from 100 bars, lead time 3 – 4 weeks. For precise lead time, contact your Customer Service manager.

SKU	PCS. per BOX	WEIGHT per	
		BOX, kg	PCS, kg
BLBP-340A10x3065E12	40	44.7	0.165
BLBP-330A10x3065I12	80	20.55	0.0745