

The MINI HE LED module is specifically engineered for uniform illumination in shallow depth and narrow channel letters, delivering exceptional performance and energy efficiency up to 160 lm/W. This module comes in diifferent whites, red, green, and blue colours. MINI HE also features a 24V version, available in various white color temperatures and red, enhancing its versatility for backlit and halo-lit applications with depths ranging from 20 mm to 60 mm and widths as narrow as 9 mm. With a distance of 86 mm between modules, the MINI HE ensures superior illumination uniformity, making it an ideal choice for precise and reliable installations.

APPLICATION

- · Shallow depth narrow channel letters
- Recommended depth 20 60 mm

FEATURES & BENEFITS

- Extremely small size
- High efficacy up to 160 lm/W
- Compact design
- Available in both 12 VDC and 24 VDC versions
- IP65 protection class
- 5-year warranty












GENERAL SPECIFICATIONS


SUPPLY VOLTAGE	12 VDC 24 VDC
POWER	0.2 W
RECOMMENDED DEPTH	From 20 to 60 mm
CC DISTANCE	86 mm
BINNING	3 SDCM
OPERATING TEMPERATURE	-20 °C ~ +50 °C
STORAGE TEMPERATURE	-30°C~+60°C
STORAGE CONDITIONS	Relative humidity <60%
IP CLASS	IP65
CERTIFICATION	CE, RoHS and UKCA compliant
LIFETIME	L70 50,000 h
WARRANTY	5 vears*





Dimensions are in mm

LIGHT DISTRIBUTION GRAPH



Beam angle: 160°

ORDERING INFORMATION

SKU	VOLTAGE	POWER*	LUMEN OUTPUT*	COLOUR TEMP.
BMP-5M-H765E0.2	12 VDC	0.2 W	32	6500 K
BMP-5M-H740E0.2	12 VDC	0.2 W	32	4000 K
BMP-5M-H730E0.2	12 VDC	0.2 W	30	3000 K
BMP-5M-H7RE0.2	12 VDC	0.2 W	10	Red
BMP-5M-H7GE0.2	12 VDC	0.2 W	18	Green
BMP-5M-H7BE0.2	12 VDC	0.2 W	3	Blue
BMP-5M-H765E0.2-24V	24 VDC	0.2 W	32	6500 K
BMP-5M-H740E0.2-24V	24 VDC	0.2 W	32	4000 K
BMP-5M-H730E0.2-24V	24 VDC	0.2 W	30	3000 K
BMP-5M-H7RE0.2-24V	24 VDC	0.2 W	10	Red

*With an acceptable margin of error of $\pm~5\%$

ORDERING QUANTITY

	CHAIN	BAG	BOX
12 VD0	40 pcs.	80 pcs.	3360 pcs.
24 VD0	80 pcs.	80 pcs.	3360 pcs.

NOTE: Modules are sold in full bags only, with a minimum order of one bag.

© 2024, All rights reserved BaltLED, UAB. Specifications are subject to change without notice.