

EDGE LIT BAR

5 YEARS WARRANTY

100 - 250

15x45°


6500 K

2250 lm

30 W


IP 67

L70 50 000 h



GENERAL SPECIFICATIONS

| | |
|-----------------------|---|
| SUPPLY VOLTAGE | 24 VDC |
| POWER, W | 10 W 17 W 30 W |
| CRI | 80 |
| OPTICS | 15x45° |
| RECOMMENDED DEPTH | 100-250 mm |
| BINNING | 3 SDCM |
| COLOUR / CCT | 6500 K |
| OPERATING TEMPERATURE | -30 °C ~ +50 °C |
| STORAGE TEMPERATURE | +5 °C ~ +70 °C |
| CERTIFICATION | CE and RoHS compliant |
| IP CLASS | IP67 IP20 |
| LIFETIME | L70 50,000 h |
| WARRANTY | 5 years |
| MOUNTING OPTIONS | IP 67: u shape snap-in clicks IP 20: double-sided tape |



ITEM DESCRIPTION

EdgeLit rigid bars are specially designed for double-sided lightboxes with depth from 100 to 250 mm and height up to 3000 mm. Depending on the model, each EdgeLit rigid bar has from 5 to 18 LEDs coupled with lenses and mounted on the aluminum bar. Thanks to that, it takes much less time to install bars than regular LED modules. It is a perfect solution to achieve homogeneous and powerful illuminance of the diffusive surface.


APPLICATION

- Double-sided light boxes
- Recommended depth: 100-250 mm

FEATURES & BENEFITS

- IP67 protection class for outdoor and indoor applications
- IP20 protection class for indoor applications
- 6 mm aluminium base for good heat sinking (for IP67 bar)
- Easy and fast installation
- Long life-span of 50,000 h
- 5-years warranty

LIGHT DISTRIBUTION GRAPH



— C0-180 - - C90-270 15x45°

ORDERING INFORMATION

| SKU | IP CLASS | COLOUR | POWER, W | LUMEN OUTPUT, LM | DIMENSIONS, MM |
|----------------------|--------------------------|--------|----------|------------------|----------------|
| BLBP-340A15x4565E10 | IP67 | 6500 K | 10.0 | 750 | 340x28x26 |
| BLBP-560A15x4565E17 | IP67 | 6500 K | 17.0 | 1275 | 560x28x26 |
| BLBP-1000A15x4565E30 | IP67 | 6500 K | 30.0 | 2250 | 1000x28x26 |
| BLBP-330A15x4565I10 | IP20 | 6500 K | 10.0 | 750 | 330x25x16 |
| BLBP-550A15x4565I17 | IP20 | 6500 K | 17.0 | 1275 | 550x25x16 |
| BLBP-990A15x4565I30 | IP20 | 6500 K | 30.0 | 2250 | 990x25x16 |
| BLBP-CKIT | Additional connector kit | | | | |

PACKAGING INFORMATION

| SKU | PCS. per BOX |
|----------------------|--------------|
| BLBP-340A15x4565E10 | 120 |
| BLBP-560A15x4565E17 | 80 |
| BLBP-1000A15x4565E30 | 40 |
| BLBP-330A15x4565I10 | 120 |
| BLBP-550A15x4565I17 | 80 |
| BLBP-990A15x4565I30 | 40 |

© 2024, All rights reserved BaltLED, UAB. Specifications are subject to change without notice.

www.baltled.com
October 24, 2024

baltled
signage illumination