


SIGNBRIDGE

BPS-24-12/24V.2



FEATURES

- Plastic housing design
- IP67 rating for indoor or outdoor installations
- 3 years warranty

CONFORMITY & STANDARDS

Security Standard:

- IEC 61347-2-13 2014+A1

Electrical Safety:

- Withstand Voltage: I/P-O/P: 3000VAC/1min/<5mA
- Isolation Resistance:
I/P-O/P: >100M Ohms / 500VDC / 25°C / 70%RH




GENERAL SPECIFICATIONS

EFFICIENCY	85% (230 VAC)
COLD START	1500 ms (230 VAC)
OPERATING CONDITIONS	-25°C ~ +50°C; 20 ~ 95% humidity
STORAGE CONDITIONS	-40°C ~ +80°C; 10 ~ 95% humidity
IP CLASS	IP67
PROTECTIONS INCLUDED	Overload Short circuit
WARRANTY	3 years

QUANTITY OF DRIVERS PER CIRCUIT BREAKER

CIRCUIT BREAKER OF TYPE B 16	CIRCUIT BREAKER OF TYPE C 16 A
9 units (230 VAC)	17 units (230 VAC)

DIMENSIONS (MM)



INPUT

INPUT VOLTAGE RANGE	100 – 250 VAC; 50 – 60 Hz
MAX INPUT AC CURRENT	0.52 A Max
MAX INRUSH CURRENT	40 A
POWER FACTOR	≥0.6 (230 VAC)

OUTPUT

CURRENT VOLTAGE	12 V 2 A 24 V 1 A
OUTPUT POWER	24 W

ORDERING INFORMATION

SKU	VOLTAGE	UNIT NET WEIGHT, G	UNIT DIMENSIONS (LxWxH), MM	PCS / BOX
BPS-24-12V.2	12 VDC	165.0	120 x 35 x 26	80
BPS-24-24V.2	24 VDC	165.0	120 x 35 x 26	80