


EDGELIT LITE BAR



IP20

IP67

ITEM DESCRIPTION

Edgelit Lite is a cost-effective solution for illuminating double-sided lightboxes with a depth of 80-150 mm and a height of up to 1500 mm. Designed for easy and fast installation, it offers the perfect balance between performance and affordability, ensuring homogeneous and powerful illumination of the diffusive surface. Whether for indoor or outdoor signage, Edgelit Lite provides a reliable and affordable alternative to standard Edgelit bars without compromising quality.

APPLICATION


- Double-sided light boxes
- Recommended depth: 80-150 mm

FEATURES & BENEFITS


- Available in IP67 for outdoor applications and IP20 for indoor use
- Easy and fast installation
- Long life-span of 54,000 h
- 5-years warranty

GENERAL SPECIFICATIONS

SUPPLY VOLTAGE	24 VDC
POWER, W	18 W
CRI	80
OPTICS	10x45°
RECOMMENDED DEPTH	80-150 mm
BINNING	5 SDCM
COLOUR / CCT	6500 K
OPERATING TEMPERATURE	-30 °C ~ +50 °C
STORAGE TEMPERATURE	+5 °C ~ +70 °C
CERTIFICATION	CE, RoHS and UKCA compliant
IP CLASS	IP67 IP20
LIFETIME	L70 54,000 h
WARRANTY	5 years
MOUNTING OPTIONS	IP 67: u shape snap-in clicks IP 20: double-sided tape



LIGHT DISTRIBUTION GRAPH



ORDERING INFORMATION

SKU	IP CLASS	COLOUR	POWER, W	LUMEN OUTPUT, LM	DIMENSIONS, MM
BLBP-1000A10x4565E18-LT	IP67	6500 K	18.0	2448	965x23x10
BLBP-1000A10x4565I18-LT	IP20	6500 K	18.0	2448	960x17x9
BLBP-LTKIT-2-IP67	Edgelit Lite accessory connector cable (200mm 20AWG 2pin DC connector IP67 male)				
BLBP-LTKIT-2-IP20	Edgelit Lite accessory connector cable (200mm 20AWG 2pin DC connector IP20 male)				

PACKAGING INFORMATION

	PCS. per BOX
IP20	40
IP67	40